

5/2-directional valve, Series TC08


0820260004

Series

TC08

2025-10-23

AVENTICS Series TC08 Directional valves



Technical data

Industry

Activation

Valve type

Switching principle

Sealing principle

Connection type

Industrial

Pneumatically

Spool valve, positive overlapping

5/2, double air pilot

Soft seal

Pipe connection

Compressed air connection input

G 1/8

Compressed air connection output

G 1/8

Compressed air connection, exhaust

G 1/8

Compressed air connection pilot input

M5

Nominal flow Qn

800 l/min

Flow conductance b

0.36

Flow conductance C

3.5 l/(s*bar)

Min. working pressure

-0.9 bar

Max. working pressure

10 bar

Min. control pressure

2.5 bar

5/2-directional valve, Series TC08

0820260004

Series

TC08

2025-10-23

Max. control pressure	10 bar
Pilot	External
Min. ambient temperature	-10 °C
Max. ambient temperature	50 °C
Min. medium temperature	-10 °C
Max. medium temperature	50 °C
Medium	Compressed air
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	5 mg/m ³
Max. particle size	5 µm
Mounting on manifold strip	P-strip
Mounting screw tightening torque	2 Nm
Weight	0.097 kg

Material

Housing material	Polyamide, fiber-glass reinforced
Seal material	Acrylonitrile butadiene rubber
Material, front cover	Polyamide, fiber-glass reinforced
Material threaded bushing	Brass
	Die cast zinc
Surface threaded bushing	chrome-plated
	nickel-plated
Part No.	0820260004

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).


5/2-directional valve, Series TC08

0820260004

Series
TC08

2025-10-23

Control pressure



P_e = external control pressure, min.
 P_B = Working pressure

5/2-directional valve, Series TC08

0820260004

Series
TC08

2025-10-23

Dimensions

