Check-choke valve, Series CC01

0821200008

2024-01-11

• Qn = 32 l/min ... 5600 l/min

AVENTICS Series CC01 Check-choke valves

The AVENTICS Series CC check-choke valves are designed for nominal flows from 32 to 5,600 l/min. The different versions are available with a push-in fitting or internal thread.





Technical data

Industry Industrial Port 1 G 1/8 Port 2 G 1/8 Throttle bore Ø 2 mm direction of throttle 1 > 2 2 > 1 Nominal flow Qn 1 to 2 130 l/min Compressed air connection type 1 Internal thread Compressed air connection type 2 Internal thread Medium Compressed air 0.5 bar Min. working pressure Max. working pressure 10 bar 0°C Min. ambient temperature 80 °C Max. ambient temperature 0°C Min. medium temperature 80 °C Max. medium temperature Weight 0.04 kg

2024-01-11

Material

0821200008

Housing material Aluminum Surface housing anodized

Seal material Acrylonitrile butadiene rubber

Material flow control screw Steel, chrome-plated

Surface flow control screw galvanized
Part No. 0821200008

Technical information


The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in https://www.emerson.com/en-us/support).

Dimensions



¹⁾ throttle setting range 2) nut for control panel installation 3) protective cap

Part No.	Port G	R1	B1	D1	D2	D3	H1	H2	H3
0821200009	G 1/8	G 1/8	16	10	M12x1	4.5	20	4	4
0821200008	G 1/8	G 1/8	16	10	M12x1	4.5	20	4	4
0821200005	G 1/4	G 1/4	25	13	M20x1,5	5.5	32	5.5	6

Part No.	H4	H5	H6	H7	H8	H9	H10	L1	L2
0821200009	56	16.5	8	8	35	4	3.5	35	25
0821200008	56	16.5	8	8	35	4	3.5	35	25
0821200005	70	26	15	11	40	5	3.5	55	38

Part No.	L3	SW1	SW2
0821200009	8	10	17
0821200008	8	10	17
0821200005	12	13	24