

Coupling plug with internal thread



1823373002

Series CP1

2025-12-03

AVENTICS Series CP1 Couplings

The AVENTICS Series CP1 of safe couplings using single snap-on coupling are robust and safe.



Technical data

Industry	Industrial
Port D	NW 7,2
Port G	G 3/8
Compressed air connection type	Coupling plug
Nominal width NW	7.2 mm
Nominal flow Qn	1450 l/min
Min. working pressure	0 bar
Max. working pressure	35 bar
Min. ambient temperature	-20 °C
Max. ambient temperature	100 °C
Min. medium temperature	-20 °C
Max. medium temperature	100 °C
Medium	Compressed air
Delivery unit	10 piece
Weight per piece	0.025 kg
Housing material	Brass
Surface housing	nickel-plated
	1823373002

Coupling plug with internal thread

1823373002

Series CP1


2025-12-03

Technical information

Nominal flow Q_n at 6 bar and $\Delta p = 1$ bar

Coupling plugs with a nominal width of NW7.2 can be used for all self sealing and safety couplings with both NW7.2 (brass) and NW7.8 (steel).

Dimensions



Part No.	Port G	Nominal width NW	L	SW
1823373001	G 1/4	7,2 mm	33	17
1823373002	G 3/8	7,2 mm	33	19
8939200504	G 1/2	7,2 mm	36	24