

# Blanking screw, gasket

2024-03-21

1823462030

## AVENTICS Blanking screws and connectors



### Technical data

|                          |            |
|--------------------------|------------|
| Industry                 | Industrial |
| Port G                   | G 3/8      |
| Type                     | FPT-S-RBI  |
| Min. working pressure    | 0 bar      |
| Max. working pressure    | 16 bar     |
| Min. ambient temperature | -20 °C     |
| Max. ambient temperature | 80 °C      |
| Delivery unit            | 25 piece   |

### Material


|               |                      |
|---------------|----------------------|
| Material      | Steel, chrome-plated |
| Surface       | galvanized           |
| Seal material | Polyvinyl chloride   |
| Surface seals | hard                 |
| Part No.      | 1823462030           |

### Dimensions

# Blanking screw, gasket

2024-03-21

1823462030



| Part No.   | Port G | Ø E | H  | L1 | SW1 |
|------------|--------|-----|----|----|-----|
| 1823462028 | G 1/8  | 14  | 8  | 3  | 5   |
| 1823462029 | G 1/4  | 18  | 12 | 3  | 6   |
| 1823462030 | G 3/8  | 22  | 12 | 3  | 8   |
| 1823462031 | G 1/2  | 26  | 14 | 4  | 10  |
| 1823462032 | G 3/4  | 32  | 16 | 4  | 12  |
| 1823462033 | G 1    | 39  | 16 | 5  | 17  |