

ISO 15407-1, Base and end plates



Technical data

Industry

Industrial

Type

Manifold strip

Compressed air connection input

G 1/8

Direction of pneumatic port (2,4)

On the side

Compressed air connection output

M5

Port exhaust

G 1/8

Exhaust (3,5)

With directional exhaust (3/5)

Type

Single plug-in wiring

Min. working pressure

0 bar

Max. working pressure

10 bar

Medium

Compressed air

Max. number of valve positions

10

Grid dimension

23 mm

Mounting screw

M3

Weight

0.427 kg

2024-09-30

Manifold block, Series DO22, G 1/8 / M5

2024-09-30

1825503600

Part No.	e1	e2	e3	e4	e5	e6	e7	e8	e9
1825503592	22	23	–	–	–	–	–	–	–
1825503593	22	23	46	–	–	–	–	–	–
1825503594	22	23	46	69	–	–	–	–	–
1825503595	22	23	46	69	92	–	–	–	–
1825503596	22	23	46	69	92	115	–	–	–
1825503597	22	23	46	69	92	115	138	–	–
1825503598	22	23	46	69	92	115	138	161	–
1825503599	22	23	46	69	92	115	138	161	184
1825503600	22	23	46	69	92	115	138	161	184

Part No.	e10	e11	l
1825503592	–	57	67
1825503593	–	80	90
1825503594	–	103	113
1825503595	–	126	136
1825503596	–	149	159
1825503597	–	173	182
1825503598	–	195	205
1825503599	–	218	228
1825503600	207	241	251