


Supply plate, stacked vertically

1825504035

ISO 15407-1, Base and end plates



Technical data

Industry
Industrial

Type
Base plate

Direction of pneumatic port (1)
On the side

Frame size
26 mm

Standards
ISO 15407-1

Working pressure min.
-0.95 bar

Working pressure max
16 bar

Min. ambient temperature
-15 °C

Max. number of valve positions
1

Mounting screw
with hexagon socket

Compressed air connection input
G 1/4

Exhaust type
Ports separated

Exhaust (3,5)
With directional exhaust (3/5)

Max. ambient temperature
70 °C

Min. medium temperature
-15 °C

Max. medium temperature
70 °C

Medium
Compressed air

Tightening torque for mounting screws
2.5 Nm

Weight
0.112 kg

Material

Material base plate
Aluminum

Seal material
Acrylonitrile butadiene rubber

Part No.
1825504035

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

Dimensions

