


Pilot valve, Series DO35

1827414008

General series information
AVENTICS Series DO Directional valves

- The AVENTICS Series DO offer a simple, reliable and robust solution for all classical pilot control functions with direct electrical operation.



Technical data

Industry	Industrial
Activation	Electrically
Compressed air connection, exhaust	G 1/8
Working pressure min.	0 bar
Working pressure max	10 bar
DC operating voltage	12 V
Manual override	with detent
Electrical connection type	Plug
Electrical connection size	EN 175301-803, form A
Valve type	Poppet valve
Sealing principle	Soft Seal
Connection type	Pipe connection

Min. ambient temperature	-10 °C
Max. ambient temperature	50 °C
Medium	Compressed air
Nominal flow Qn 1 to 2	100 l/min
Nominal flow Qn 2 to 3	120 l/min
Duty cycle	100 %
mounting screws	M4
Mounting screw tightening torque	1 Nm
Tightening torque tolerance	+0,3

Material

Seal material	Fluorocaoutchouc
Part No.	1827414008

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).