

## Schmierfette und Öle



Fette und Öle



## Produktübersicht

### Schmiermittel

	Seite
Fett.....	4
Öl.....	5
Pneumatic Oil AOF.....	6

Fett



Umgebungs-temperatur min. [°C]	Umgebungs-temperatur max. [°C]	Dichte [g/cm <sup>3</sup> ]	Kinematische Viskosität [cSt]	Behälter	Silikon	Materialnummer
-40	100	0.85	150	Tube	silikonfrei	8315020734
-40	100	0.85	150	Kartusche	silikonfrei	8315020724
-40	100	0.85	150	Dose	silikonfrei	8315020764
-25	100	0.89	280	Tube	silikonhaltig	8981050000
-30	100	0.9	400	Tube	silikonfrei	R499001048
-30	100	0.9	400	Kartusche	silikonfrei	R499002843
-30	150	1.95	200	Tube	silikonfrei	R412023904

Öl



Flamm- punkt min. [°C]	Stock- punkt min. [°C]	Dichte [g/cm <sup>3</sup> ]	Viskosi- tätsklasse	Kinemat- sche Vis- kosität [cSt]	Behälter	Materialnummer
188	-42	0.87	ISO VG 32	35.9	Flasche	8982000010

Pneumatic Oil AOF







Mediums-temperatur min. [°C]	Mediums-temperatur max. [°C]	Viskositätsklasse	Kinematische Viskosität [cSt]	Behälter	Materialnummer
-45	110	ISO VG 15	15	Dose	R499002207

Efficient pneumatic solutions, our program:  
cylinders and drives, valves and valve systems,  
air supply management, proportional pressure  
control valves



Visit us: [www.Emerson.com/aventics](http://www.Emerson.com/aventics)  
Your local contact: [Emerson.com/contactus](http://Emerson.com/contactus)

-  [Emerson.com](http://Emerson.com)
-  [Facebook.com/EmersonAutomationSolutions](https://Facebook.com/EmersonAutomationSolutions)
-  [LinkedIn.com/company/Emerson-Automation-Solutions](https://LinkedIn.com/company/Emerson-Automation-Solutions)
-  [Twitter.com/EMR\\_Automation](https://Twitter.com/EMR_Automation)



The Emerson logo is a trademark and service mark of Emerson Electric Co. AVENTICS is a registered trademark of one of the Emerson family of companies. All other trademarks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.



**CONSIDER IT SOLVED™**