

Grease and oils



Grease and oils



Product overview

Lubricant

	Page
Grease.....	4
Oil.....	5
Pneumatic Oil AOF.....	6

Grease



Min. ambient temperature [°C]	Max. ambient temperature [°C]	Density [g/cm ³]	Kinematic viscosity [cSt]	Reservoir	Silicon	Part No.
-40	100	0.85	150	Tube	silicone-free	8315020734
-40	100	0.85	150	Cartridge	silicone-free	8315020724
-40	100	0.85	150	Socket	silicone-free	8315020764
-25	100	0.89	280	Tube	contains silicon	8981050000
-30	100	0.9	400	Tube	silicone-free	R499001048
-30	100	0.9	400	Cartridge	silicone-free	R499002843
-30	150	1.95	200	Tube	silicone-free	R412023904

Oil



Min. flash point [°C]	Min. pour point [°C]	Density [g/cm ³]	Viscosity class	Kinematic viscosity [cSt]	Reservoir	Part No.
188	-42	0.87	ISO VG 32	35.9	Bottle	8982000010

Pneumatic Oil AOF







Min. medium temperature [°C]	Max. medium temperature [°C]	Viscosity class	Kinematic viscosity [cSt]	Reservoir	Part No.
-45	110	ISO VG 15	15	Socket	R499002207

Efficient pneumatic solutions, our program:
cylinders and drives, valves and valve systems,
air supply management, proportional pressure
control valves



Visit us: www.Emerson.com/aventics
Your local contact: Emerson.com/contactus

-  Emerson.com
-  Facebook.com/EmersonAutomationSolutions
-  LinkedIn.com/company/Emerson-Automation-Solutions
-  Twitter.com/EMR_Automation



The Emerson logo is a trademark and service mark of Emerson Electric Co. AVENTICS is a registered trademark of one of the Emerson family of companies. All other trademarks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.



CONSIDER IT SOLVED™