

3/2-directional valve, Series CD12, single solenoid


5724565202

CD12

2025-12-10

AVENTICS Series CD12 Directional valves

The AVENTICS Series CD consists of various spool valves with an extremely durable die-cast zinc housing. Its electrical, pneumatic, or mechanical actuating controls (roller, lever, pedal, or plunger) make the Series CD ideal for applications in harsh environments.



Technical data

Industry	Industrial
Activation	Electrically
Valve type	Spool valve, positive overlapping
Basic valve equipment	Basic valve without pilot valve
Switching principle	3/2, with spring return
Valve function	NC/NO
Sealing principle	Soft seal
Connection type	Pipe connection
Compressed air connection type	Internal thread
Standard compressed air connection	according to ISO 228-1
Compressed air connection input	G 1/2
Compressed air connection output	G 1/2
Compressed air connection, exhaust	G 1/2
Pilot control exhaust	with directional pilot air exhaust
Compressed air connection pilot input	G 1/8
Nominal flow Qn	4000 l/min
Nominal flow Qn 1 to 2	4000 l/min

3/2-directional valve, Series CD12, single solenoid

5724565202

CD12

2025-12-10

Nominal flow Qn 2 to 3	4000 l/min
Min. working pressure	-0.95 bar
Max. working pressure	16 bar
Min. control pressure	2 bar
Max. control pressure	16 bar
Electrical connection type	Plug
Electrical connection size	EN 175301-803, form A
Electrical connection number of poles	3-pin
Connector standard	EN 175301-803:2006
Pilot	External
Coil width	30 mm
Pilot valve width	30 mm
Duty cycle	100 %
Temperature resistance	-25 °C cold-resistant
ATEX	ATEX optional
Min. ambient temperature	-25 °C
Max. ambient temperature	70 °C
Min. medium temperature	-25 °C
Max. medium temperature	70 °C
Medium	Compressed air
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	1 mg/m ³
Max. particle size	50 µm
Weight	0.7 kg
Material	
Housing material	Aluminum Polyamide, fiber-glass reinforced
Seal material	Acrylonitrile butadiene rubber Polyurethane
Part No.	5724565202

3/2-directional valve, Series CD12, single solenoid

5724565202

CD12

2025-12-10

Technical information

ATEX optional: ATEX version can be produced by combining the basic valve without coil with an ATEX coil. ATEX ID: see ATEX coils catalog page.

option valve: The input and output compressed air connections can be exchanged. The valve can thereby be used in the NC or NO operating mode.

*Note: Basic valves feature a maximum working pressure of 16 bar. When combined with standard CNOMO pilots, the maximum working pressure is 10 bar.

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

