

5/3-directional valve, Series CD12, double solenoid


5725655980

CD12

2025-12-10

AVENTICS Series CD12 Directional valves

The AVENTICS Series CD consists of various spool valves with an extremely durable die-cast zinc housing. Its electrical, pneumatic, or mechanical actuating controls (roller, lever, pedal, or plunger) make the Series CD ideal for applications in harsh environments.



Technical data

Industry

Activation

Valve type

Switching principle

Valve function

Sealing principle

Connection type

Manual override

Industrial

Electrically

Spool valve, positive overlapping

5/3, closed center

Closed Center

Soft seal

Pipe connection

with detent

Compressed air connection type

Standard compressed air connection

Compressed air connection input

Compressed air connection output

Compressed air connection, exhaust

Pilot control exhaust

Internal thread

according to ISO 228-1

G 1/2

G 1/2

G 1/2

with directional pilot air exhaust

Nominal flow Q_n

Nominal flow Q_n 1 to 2

Nominal flow Q_n 2 to 3

3800 l/min

3800 l/min

3800 l/min

5/3-directional valve, Series CD12, double solenoid

5725655980

CD12

2025-12-10

Min. working pressure	3 bar
Max. working pressure	10 bar
Min. control pressure	3 bar
Max. control pressure	10 bar
Electrical connection type	Plug
Electrical connection size	EN 175301-803, form A
Electrical connection number of poles	3-pin
Connector standard	EN 175301-803:2006
Protection class with connection	IP65
Reverse polarity protection	Protected against polarity reversal
Operational voltage	230 V AC
Operational voltage AC at 50 Hz	230 V
Voltage tolerance AC 50 Hz	-20 % / +10 %
Operational voltage AC at 60 Hz	230 V
Voltage tolerance AC 60 Hz	-10 % / +20 %
Pilot	Internal
Coil width	30 mm
Pilot valve width	30 mm
Compatibility index	52
Holding power AC 50 Hz	4.4 VA
Holding power AC 60 Hz	3.5 VA
Switch-on power AC 50 Hz	6.9 VA
Switch-on power AC 60 Hz	6.2 VA
Duty cycle	100 %
Typ. switch-on time	37 ms
Typ. switch-off time	97 ms
Min. ambient temperature	-15 °C
Max. ambient temperature	50 °C
Min. medium temperature	-15 °C
Max. medium temperature	50 °C
Medium	Compressed air
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	1 mg/m ³
Max. particle size	50 µm

5/3-directional valve, Series CD12, double solenoid

5725655980

CD12

2025-12-10

Weight 1.3 kg

Material

Housing material	Aluminum Polyamide, fiber-glass reinforced
Seal material	Acrylonitrile butadiene rubber Polyurethane

Part No. 5725655980

Technical information

ATEX optional: ATEX version can be produced by combining the basic valve without coil with an ATEX coil. ATEX ID: see ATEX coils catalog page.

*Note: Basic valves feature a maximum working pressure of 16 bar. When combined with standard CNOMO pilots, the maximum working pressure is 10 bar.

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

5725655980

CD12

2025-12-10

Technical drawing of a 12V 100Ah battery, showing three views: front, side, and top.

Front View (Left): Shows the battery terminals (G1/8) and the main body. Dimensions include a total height of 247 mm, a main body height of 174 mm, and a terminal height of 28 mm. The terminal diameter is Ø8.8 mm. The main body has a width of 74 mm and a depth of 68 mm. The terminal diameter is Ø8.8 mm. The main body has a width of 74 mm and a depth of 68 mm.

Side View (Right): Shows the battery terminals (G1/8) and the main body. Dimensions include a total height of 247 mm, a main body height of 174 mm, and a terminal height of 28 mm. The terminal diameter is Ø8.8 mm. The main body has a width of 74 mm and a depth of 68 mm. The terminal diameter is Ø8.8 mm. The main body has a width of 74 mm and a depth of 68 mm.

Top View (Bottom): Shows the battery terminals (G1/8) and the main body. Dimensions include a total height of 247 mm, a main body height of 174 mm, and a terminal height of 28 mm. The terminal diameter is Ø8.8 mm. The main body has a width of 74 mm and a depth of 68 mm. The terminal diameter is Ø8.8 mm. The main body has a width of 74 mm and a depth of 68 mm.

- 