

5/2-directional valve, Series CD07, double solenoid

5776625280

CD07


2025-12-08

AVENTICS Series CD07 Directional valves

The AVENTICS Series CD consists of various spool valves with an extremely durable die-cast zinc housing. Its electrical, pneumatic, or mechanical actuating controls (roller, lever, pedal, or plunger) make the Series CD ideal for applications in harsh environments.

For demanding environments

- Durable design
- Assembly on base plate
- Suitable for extreme ambient temperatures
- ATEX version available



Technical data

Industry

Activation

Note

Frame size

Valve type

Switching principle

Sealing principle

Connection type

Manual override

Industrial

Electrically operated

Valves with Namur port as per VDI/VDE3845

CD07

Spool valve, positive overlapping

5/2, double solenoid

Soft seal

Pipe connection

with detent

Compressed air connection

Compressed air connection type

Standard compressed air connection

Compressed air connection input

Compressed air connection output

Compressed air connection, exhaust

Pilot control exhaust

Compressed air connection pilot exhaust

G 1/4

Base plate connection

Internal thread

according to ISO 228-1

G 1/4

Namur base plate

G 1/4

with directional pilot air exhaust

M5

Nominal flow Qn

1200 l/min

Nominal flow Qn 1 to 2

1200 l/min

Nominal flow Qn 2 to 3

1200 l/min

5/2-directional valve, Series CD07, double solenoid

5776625280

CD07

2025-12-08

Min. working pressure	2 bar
Max. working pressure	10 bar
Min. control pressure	2 bar
Max. control pressure	10 bar
Electrical connection type	Plug
Electrical connection size	EN 175301-803, form A
Electrical connection number of poles	3-pin
Connector standard	EN 175301-803:2006
Protection class with connection	IP65
Reverse polarity protection	Protected against polarity reversal
Operational voltage AC at 50 Hz	230 V
Voltage tolerance AC 50 Hz	-20 % / +10 %
Operational voltage AC at 60 Hz	230 V
Voltage tolerance AC 60 Hz	-10 % / +20 %
Pilot	Internal
Coil width	30 mm
Pilot valve width	30 mm
Compatibility index	52
Holding power AC 50 Hz	4.8 VA
Holding power AC 60 Hz	4.1 VA
Switch-on power AC 50 Hz	6.9 VA
Switch-on power AC 60 Hz	5.8 VA
Duty cycle	100 %
Typ. switch-on time	21 ms
Typ. switch-off time	21 ms
Temperature resistance	-25 °C cold-resistant
Standards	NAMUR
Min. ambient temperature	-25 °C
Max. ambient temperature	50 °C
Min. medium temperature	-25 °C
Max. medium temperature	50 °C
Medium	Compressed air
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	1 mg/m ³
Max. particle size	50 µm

5/2-directional valve, Series CD07, double solenoid

5776625280

CD07

2025-12-08

Weight 0.8 kg

Material

Housing material	Die cast zinc Polyamide, fiber-glass reinforced
Seal material	Acrylonitrile butadiene rubber

Part No. 5776625280

Technical information

Nominal flow Q_n at 6 bar and $\Delta p = 1$ bar

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).


5/2-directional valve, Series CD07, double solenoid

5776625280

CD07

2025-12-08

Dimensions in mm



- 1) After removal of cap M 5 internal thread
- 2) Threaded pins DIN 914 M5 x 20
- 3) O-ring 16 x 2 (included in scope of delivery)
- 4) cylinder screw M5x40 (included in scope of delivery)