

5/2-directional valve, Series CD07, double solenoid

5776840220

CD07


2025-12-08

AVENTICS Series CD07 Directional valves

The AVENTICS Series CD consists of various spool valves with an extremely durable die-cast zinc housing. Its electrical, pneumatic, or mechanical actuating controls (roller, lever, pedal, or plunger) make the Series CD ideal for applications in harsh environments.

For demanding environments

- Durable design
- Assembly on base plate
- Suitable for extreme ambient temperatures
- ATEX version available



Technical data

Industry

Activation

Frame size

Valve type

Switching principle

Sealing principle

Connection type

Manual override

Industrial

Electrically operated

CD07

Spool valve, positive overlapping

5/2, double solenoid

Soft seal

Pipe connection

with detent

Compressed air connection

Compressed air connection type

Standard compressed air connection

Compressed air connection input

Compressed air connection output

Compressed air connection, exhaust

Pilot control exhaust

Compressed air connection pilot exhaust

G 1/4

Internal thread

according to ISO 228-1

G 1/4

G 1/4

G 1/4

with directional pilot air exhaust

M5

Nominal flow Q_n

1200 l/min

5/2-directional valve, Series CD07, double solenoid

5776840220

CD07

2025-12-08

Nominal flow Qn 1 to 2	1200 l/min
Nominal flow Qn 2 to 3	1200 l/min
Min. working pressure	3 bar
Max. working pressure	10 bar
Min. control pressure	3 bar
Max. control pressure	10 bar
Electrical connection type	Plug
Electrical connection size	EN 175301-803, form A
Electrical connection number of poles	3-pin
Connector standard	EN 175301-803:2006
Protection class with connection	IP65
Reverse polarity protection	Protected against polarity reversal
Operational voltage	24 V DC
Operational voltage DC	24 V
Voltage tolerance DC	-10 % / +10 %
Pilot	Internal
Coil width	30 mm
Pilot valve width	30 mm
Compatibility index	52
Power consumption DC	2.1 W
Duty cycle	100 %
Typ. switch-on time	21 ms
Typ. switch-off time	21 ms
Temperature resistance	-40 °C cold-resistant
Min. ambient temperature	-40 °C
Max. ambient temperature	50 °C
Min. medium temperature	-40 °C
Max. medium temperature	50 °C
Medium	Compressed air
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	1 mg/m ³
Max. particle size	50 µm
Mounting on manifold strip	P-strip PRS strip
Weight	0.75 kg

5/2-directional valve, Series CD07, double solenoid

5776840220

CD07

2025-12-08

Material

Housing material

Die cast zinc

Polyamide, fiber-glass reinforced

Seal material

Polyurethane

Part No.

5776840220

Technical information

Nominal flow Q_n at 6 bar and $\Delta p = 1$ bar

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

2025-12-08

Technical drawing of a 5-position selector switch, showing three views: front view (left), side view (middle), and top view (right). Dimensions are in millimeters.

Front View (Left):

- Overall height: 199 mm
- Overall width: 55 mm
- Mounting holes: 2 mm diameter, 3 mm spacing
- Indicator windows: 29 mm diameter, 22 mm spacing
- Switch mechanism: 25 mm diameter, 6 mm spacing
- Internal components: 14 mm diameter, 5 mm spacing
- Bottom mounting: 42 mm diameter, 0.5 mm spacing

Side View (Middle):

- Overall height: 199 mm
- Overall width: 55 mm
- Mounting holes: 2 mm diameter, 3 mm spacing
- Indicator windows: 29 mm diameter, 22 mm spacing
- Switch mechanism: 25 mm diameter, 6 mm spacing
- Internal components: 14 mm diameter, 5 mm spacing
- Bottom mounting: 42 mm diameter, 0.5 mm spacing

Top View (Right):

- Overall width: 30 mm
- Mounting holes: 2 mm diameter, 3 mm spacing
- Indicator windows: 29 mm diameter, 22 mm spacing
- Switch mechanism: 25 mm diameter, 6 mm spacing
- Internal components: 14 mm diameter, 5 mm spacing
- Bottom mounting: 42 mm diameter, 0.5 mm spacing

- 4