


AVENTICS Series 490/579/589 Directional Control Valves

The AVENTICS Series 490/579/589 have a robust polymer housing that can be mounted individually or as a block. They cover a large range of voltages and feature fast connections for pneumatic tubing.

- Integrated connections
- Individual or block assemblies available
- Extensive voltage range
- Series suitable for dusty environments



Technical data

Industry	Industrial
Activation	Electrically
Frame size	579
Valve type	Poppet valve
Switching principle	3/2, with spring return
Valve function	NC
Sealing principle	Soft seal
Connection type	Pipe connection
Compressed air connection type	Push-in fitting
Compressed air connection input	Ø 8x1
Compressed air connection output	Ø 8x1
Compressed air connection pilot input	Ø 4
Nominal flow Q _n	850 l/min
Min. working pressure	0.5 bar
Max. working pressure	8 bar
Min. control pressure	2 bar

3/2-directional valve, Series 579, Valve unit

5790670620

Series
490/579/589

2025-12-11

Max. control pressure	8 bar
Electrical connection type	Plug
Electrical connection size	ISO 15217, form C
Protection class with connection	IP65
Reverse polarity protection	Protected against polarity reversal
Operational voltage	24 V DC
Operational voltage DC	24 V
Voltage tolerance DC	-10 % / +10 %
Pilot	External
Coil width	20 mm
LED status display	Red
Power consumption DC	1.7 W
Duty cycle	100 %
Typ. switch-on time	18 ms
Typ. switch-off time	16 ms
Blocking principle	Inlet valve
Can be assembled into blocks	Can be assembled into blocks
Min. ambient temperature	-15 °C
Max. ambient temperature	50 °C
Min. medium temperature	-15 °C
Max. medium temperature	50 °C
Medium	Compressed air
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	1 mg/m ³
Max. particle size	5 µm
Weight	0.093 kg
Material	
Housing material	Polyamide
Seal material	Acrylonitrile butadiene rubber Polyurethane
Part No.	5790670620

Technical information

At an ambient temperature of $[[40]]^{\circ}\text{C}$ the max. working pressure is $[[10]]\text{ bar}$.

Versions with voltage of less than 50 V DC do not have a protective ground.

The control pressure must be at least as high as the working pressure.

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15°C less than ambient and medium temperature and may not exceed 3°C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

5790670620

2025-12-11

Technical drawing of the 3000 series three-way solenoid valve, showing front, side, and top views with detailed dimensions and callouts.

Front View (Left):

- Callouts: 4) (Screw), 7) (Screw), 9) (Body), 1) (Port), 12) (Port).
- Dimensions: 18,6 (Port height), 1,5 (Port offset), 23 (Body width), 30 (Total width).

Side View (Top):

- Callouts: 8) (Screw), 6) (Port), 3) (Screw), 2) (Port).
- Dimensions: 41,5 (Total width), 41,1 (Body width), 15,5 (Port offset), 14 (Port height), 12 (Port offset), 13 (Port offset), 6 (Port offset), 3,9 (Port offset), 3,5 (Port offset), 14 (Port height), 22,3 (Port height), 44,3 (Total height), 7 (Port offset), 2,6 (Port offset), 15,3 (Port offset), 35,4 (Port offset), 5,8 (Port offset), 43 (Port offset), 61 (Total width), 5 (Port offset).

Top View (Bottom):

- Callouts: 5) (Screw), 1) (Port), 12) (Port).
- Dimensions: 4,1 (Port offset), 27,7 (Port offset), 7,3 (Port offset), 10 (Port offset).

Front View (Right):

- Callouts: 3) (Screw), 2) (Port).
- Dimensions: 74,2 (Total height), 20 (Port offset), 15,4 (Port offset), 28 (Port offset), 9 (Port offset), 16,3 (Port offset).

Top View (Right):

- Callouts: I, II, III (Ports), IV* (Port), 1) (Port).
- Dimensions: 12 (Port offset), 12 (Port offset), 12 (Port offset), 1 (Port offset), 1 (Port offset), 1 (Port offset).

Dimensions:

- 41,5
- 41,1
- 15,5
- 14
- 12
- 13
- 6
- 3,9
- 3,5
- 14
- 22,3
- 44,3
- 7
- 2,6
- 15,3
- 35,4
- 5,8
- 43
- 61
- 5
- 74,2
- 20
- 15,4
- 28
- 9
- 16,3
- 12
- 12
- 12
- 1
- 1
- 1

1) Port 1 2) Port 2 3) Port 3, exhaust air must not be throttled 4) Core Ø for M5 5) Pocket hole 6 mm deep for 3.5 self-tapping screw 6) Mounting space for name plate 7) Coil can be rotated at 180° intervals 8) LED 9) Port 12 * Air connection module (item IV) mounted onto stacking valve (item II) permits additional air supply from right hand side. End valve (item III) not required.
I = Inlet valve, II = Stacking valve, III = End valve