

3/2-directional valve, Series 579

5794420220

Series
490/579/589

2025-12-11

AVENTICS Series 490/579/589 Directional Control Valves

The AVENTICS Series 490/579/589 have a robust polymer housing that can be mounted individually or as a block. They cover a large range of voltages and feature fast connections for pneumatic tubing.

- Integrated connections
- Individual or block assemblies available
- Extensive voltage range
- Series suitable for dusty environments



Technical data

Industry	Industrial
Activation	Electrically
Note	External
Frame size	579
Valve type	Poppet valve
Switching principle	3/2, with spring return
Valve function	NO
Sealing principle	Soft seal
Connection type	Pipe connection
Compressed air connection type	Push-in fitting
Compressed air connection input	Ø 6x1
Compressed air connection output	Ø 6x1
Compressed air connection pilot input	Ø 4
Nominal flow Qn	520 l/min
Min. working pressure	0.5 bar
Max. working pressure	8 bar

3/2-directional valve, Series 579

5794420220

Series
490/579/589

2025-12-11

Min. control pressure	2 bar
Max. control pressure	8 bar
Electrical connection type	Plug
Electrical connection size	ISO 15217, form C
Protection class with connection	IP65
Reverse polarity protection	Protected against polarity reversal
Operational voltage	24 V DC
Operational voltage DC	24 V
Voltage tolerance DC	-10 % / +10 %
Pilot	External
Coil width	20 mm
Power consumption DC	1.6 W
Duty cycle	100 %
Typ. switch-on time	18 ms
Typ. switch-off time	16 ms
Blocking principle	Single valve
Min. ambient temperature	-15 °C
Max. ambient temperature	50 °C
Min. medium temperature	-15 °C
Max. medium temperature	50 °C
Medium	Compressed air
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	1 mg/m ³
Max. particle size	5 µm
Weight	0.093 kg

Material

Housing material	Polyamide
Seal material	Acrylonitrile butadiene rubber Polyurethane

Part No.	5794420220
----------	------------

Technical information

At an ambient temperature of $[[40]]^{\circ}\text{C}$ the max. working pressure is $[[10]]\text{ bar}$.

Versions with voltage of less than 50 V DC do not have a protective ground.

The control pressure must be at least as high as the working pressure.

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15°C less than ambient and medium temperature and may not exceed 3°C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

5794420220

2025-12-11

Technical drawing of a 3/2-way solenoid valve, showing three views: front, side, and top. The drawing includes dimensions in millimeters and callouts for specific features.

Front View (Top): Shows the main body of the valve. Dimensions include a total width of 41.5 mm, a mounting flange diameter of 41.1 mm, and a central port diameter of 15.5 mm. The height of the main body is 78 mm. Callouts 1, 2, 3, 4, 5, 6, 7, 8, and 9 point to various components.

Side View (Middle): Shows the side profile of the valve. Dimensions include a total height of 74.2 mm, a mounting flange diameter of 20 mm, and a central port diameter of 15.4 mm. Callouts 1, 2, 3, 4, 5, 6, 7, 8, and 9 point to various components.

Top View (Bottom): Shows the top of the valve. Dimensions include a total width of 27.7 mm, a mounting flange diameter of 4.1 mm, and a central port diameter of 7.3 mm. Callouts 1, 2, 3, 4, 5, 6, 7, 8, and 9 point to various components.

Dimensions:

- 41.5, 41.1, 15.5, 14, 12, 13, 6, 3.9, 3.5, 3.7, 78, 74.2, 20, 15.4, 28, 9, 16.3, 2, 1, 12, 32.2, 12.8, 9, 1.5, 23, 7, 15.3, 35.4, 5.8, 43, 67, 5, 22.3, 44.3, 14, 6, 7, 4, 2, 3, 4, 5, 6, 7, 8, 9

Callouts:

- 1: Main body
- 2: Solenoid coil
- 3: Solenoid coil mounting flange
- 4: Solenoid coil mounting flange
- 5: Solenoid coil mounting flange
- 6: Solenoid coil mounting flange
- 7: Solenoid coil mounting flange
- 8: Solenoid coil mounting flange
- 9: Solenoid coil mounting flange

1) Port 1 2) Port 2 3) Port 3, exhaust air must not be throttled 4) Core Ø for M5 5) Pocket hole 6 mm deep for 3.5 self-tapping screw 6) Mounting space for name plate 7) Coil can be rotated at 180° intervals 8) LED 9) Port 12