

AVENTICS Series 490/579/589 Directional Control Valves

The AVENTICS Series 490/579/589 have a robust polymer housing that can be mounted individually or as a block. They cover a large range of voltages and feature fast connections for pneumatic tubing.

- Integrated connections
- Individual or block assemblies available
- Extensive voltage range
- Series suitable for dusty environments



Technical data

Industry	Industrial
Activation	Electrically
Frame size	579
Valve type	Poppet valve
Switching principle	5/2, with spring return
Sealing principle	Soft seal
Connection type	Pipe connection
Manual override	with detent
Compressed air connection type	Push-in fitting
Compressed air connection input	Ø 6x1
Compressed air connection output	Ø 6x1
Nominal flow Q _n	520 l/min
Min. working pressure	2 bar
Max. working pressure	8 bar
Electrical connection type	Plug

5/2-directional valve, Series 579

5794700620

Series
490/579/589

2025-12-11

Electrical connection size	ISO 15217, form C
Protection class with connection	IP65
Reverse polarity protection	Protected against polarity reversal
Operational voltage	24 V DC
Operational voltage DC	24 V
Voltage tolerance DC	-10 % / +10 %

Pilot	Internal
Coil width	20 mm
LED status display	Red
Power consumption DC	1.7 W

Duty cycle	100 %
Typ. switch-on time	27 ms
Typ. switch-off time	28 ms

Blocking principle	Single valve
Min. ambient temperature	-15 °C
Max. ambient temperature	50 °C
Min. medium temperature	-15 °C
Max. medium temperature	50 °C
Medium	Compressed air
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	1 mg/m ³
Max. particle size	5 µm

Weight	0.133 kg
--------	----------

Material

Housing material	Polyamide
Seal material	Acrylonitrile butadiene rubber Polyurethane

Part No.	5794700620
----------	------------

Technical information

At an ambient temperature of $[[40]]^{\circ}\text{C}$ the max. working pressure is $[[10]]\text{ bar}$.

Versions with voltage of less than 50 V DC do not have a protective ground.

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15°C less than ambient and medium temperature and may not exceed 3°C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

5794700620

2025-12-11

Technical drawing of a 4-way valve, showing three views: front, side, and top. The drawing includes dimensions in millimeters and callouts for specific features.

Dimensions:

- Front View:**
 - Overall width: 46,4
 - Overall height: 44,3
 - Top flange width: 41,5
 - Top flange height: 41,1
 - Top flange thickness: 15,5
 - Top flange diameter: 14
 - Top flange hole diameter: 12
 - Top flange hole offset: 13
 - Top flange hole diameter: 6
 - Top flange hole offset: 3,9
 - Top flange hole diameter: 3,5
 - Top flange hole offset: 3,7
 - Top flange hole diameter: 1,5
 - Top flange hole offset: 1,5
 - Top flange hole diameter: 1,5
 - Top flange hole offset: 1,5
- Side View:**
 - Overall width: 41,5
 - Overall height: 44,3
 - Top flange width: 41,1
 - Top flange height: 15,5
 - Top flange thickness: 14
 - Top flange diameter: 12
 - Top flange hole diameter: 13
 - Top flange hole offset: 6
 - Top flange hole diameter: 3,9
 - Top flange hole offset: 3,5
 - Top flange hole diameter: 3,7
 - Top flange hole offset: 3,7
 - Top flange hole diameter: 1,5
 - Top flange hole offset: 1,5
 - Top flange hole diameter: 1,5
 - Top flange hole offset: 1,5
- Top View:**
 - Overall width: 46,4
 - Overall height: 44,3
 - Top flange width: 41,5
 - Top flange height: 41,1
 - Top flange thickness: 15,5
 - Top flange diameter: 14
 - Top flange hole diameter: 12
 - Top flange hole offset: 13
 - Top flange hole diameter: 6
 - Top flange hole offset: 3,9
 - Top flange hole diameter: 3,5
 - Top flange hole offset: 3,7
 - Top flange hole diameter: 1,5
 - Top flange hole offset: 1,5
 - Top flange hole diameter: 1,5
 - Top flange hole offset: 1,5

Callouts:

- 1) Port 1
- 2) Port 2
- 3) Port 3
- 4) Port 4
- 5) Port 5
- 6) Port 6
- 7) Port 7
- 8) Port 8
- 9) Port 9
- 10) Port 10
- 11) Port 11
- 12) Port 12

AVENTICS

