

Single subbase, for soft-start valve

5834710000

2024-08-15



Technical data

Industry	Industrial
Type	Base plate
Compressed air connection input	G 1/2
Compressed air connection output	G 1/2
Port exhaust	G 1/2
Exhaust type	Ports separated
Exhaust (3,5)	uncollected exhaust
Compressed air connection 14	G 1/8
Min. working pressure	-1 bar
Max. working pressure	16 bar
Min. ambient temperature	-20 °C
Max. ambient temperature	70 °C
Min. medium temperature	-20 °C
Max. medium temperature	70 °C
Medium	Compressed air
Max. number of valve positions	1
Weight	0.34 kg

Single subbase, for soft-start valve

2024-08-15

5834710000

Material

Material base plate	Die-cast aluminum
Surface base plate	black painted
Part No.	5834710000

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

Single subbase, for soft-start valve

2024-08-15

5834710000

Dimensions

