## Air supply sandwich plate, series XV05

C573AW555919009 2025-03-10

- · Optimized flow to size
- Easy and flexible custom specific configurations via online configurator
- Broad connectivity through terminal strip, multipol, or fieldbus connection
- Multiple pneumatic connection directions as side, bottom and top
- · Low energy consumption
- Wide range of accessories as shut-off, supply modules, speed modules and regulators
- · Webserver and diagnostic
- Global availability and universal threads to support regional demands
- Robust aluminium base plate and ready for cabinet assembly



The AVENTICS XV05 series provides a reliable basis for both compact handling systems and complex automation solutions. It comprises a wide range of valve functions and accessories as well as the required electrical connectivity for all requirements in factory automation and other industries. The associated XVES Connectivity module allows for connection options ranging from simple direct control via D-SUB or terminal strips to a variety of fieldbus protocols. Our one-of-a-kind online configurator makes it easy to configure the complete valve system, including accessories, so that it is perfectly tailored to your application needs.



### Technical data

Industry Industrial

Scope of delivery Sandwich plate, sealing kit, mounting screws

Min. working pressure -0.95 bar
Max. working pressure 10 bar
Min. ambient temperature -10 °C
Max. ambient temperature 50 °C

Medium Compressed air

Min. oil content of compressed air 0 mg/m³
Max. oil content of compressed air 5 mg/m³

Number of valve positions 1
Protection class IP65

Material

Housing material Aluminum, anodized

# Air supply sandwich plate, series XV05

Series XV05

C573AW555919009 2025-03-10

Seal material Screws material Part No. Hydrogenated nitrile butadiene rubber Stainless Steel C573AW555919009

#### Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in https://www.emerson.com/en-us/support).

### **Dimensions**





