Coil, Series CO1, ATEX

R412000146 2024-08-08

- · Coil widths 15, 22 and 30 mm
- Electr. control: M8, form A, form B, form BI, form C
- ATEX
- Operational voltages 12, 24, 48, 110, 220
 VDC or 24,110,230 VAC

AVENTICS Series CO1 Coils

The AVENTICS Series CO1 is a complete range of electrical solenoid coils with or without cable used in AVENTICS pneumatic valves Series.



Technical data

Industry Industrial

Type With valve plug connector

Coil width 30 mm
ATEX

II 3G Ex ec IIC T4 Gc X

II 3D Ex tc IIIC T125°C Dc X

Certificates ATEX

Min. ambient temperature -10 °C

Max. ambient temperature 50 °C

Protection class according to EN 60529 IP65

Duty cycle ED 100 %

Compatibility index 13

Operational voltage AC at 50 Hz 110 V

Operational voltage AC at 60 Hz 110 V

Voltage tolerance AC 50 Hz -10 % / +10 % Voltage tolerance AC 60 Hz -10 % / +10 %

Holding power AC 50 Hz 4 VA
Holding current AC 50 Hz 36 mA
Holding current AC 60 Hz 28 mA



Coil, Series CO1, ATEX

R412000146 2024-08-08

Switch-on power AC 50 Hz	6.8 VA
Swith-on current AC 50 Hz	62 mA
Weight	0.122 kg

Material

Part No. R412000146

Dimensions





