

5/2-directional valve, Series CD12, single solenoid


R412000242

CD12

2025-12-10

AVENTICS Series CD12 Directional valves

The AVENTICS Series CD consists of various spool valves with an extremely durable die-cast zinc housing. Its electrical, pneumatic, or mechanical actuating controls (roller, lever, pedal, or plunger) make the Series CD ideal for applications in harsh environments.



Technical data

Industry

Activation

Valve type

Basic valve equipment

Switching principle

Sealing principle

Connection type

Industrial

Electrically

Spool valve, positive overlapping

Basic valve without pilot valve

5/2, with spring return

Soft seal

Pipe connection

Compressed air connection type

Compressed air connection input

Compressed air connection output

Compressed air connection, exhaust

Pilot control exhaust

Compressed air connection pilot input

Internal thread

M22x1,5

M22x1,5

M22x1,5

with directional pilot air exhaust

G 1/8

Nominal flow Q_n

4100 l/min

Min. working pressure

-0.95 bar

Max. working pressure

16 bar

5/2-directional valve, Series CD12, single solenoid

R412000242

CD12

2025-12-10

Min. control pressure	2 bar
Max. control pressure	10 bar
Electrical connection type	Plug
Electrical connection size	EN 175301-803, form A
Electrical connection number of poles	3-pin
Pilot	External
Coil width	30 mm
Pilot valve width	30 mm
Duty cycle	100 %
Typ. switch-off time	97 ms
Temperature resistance	-25 °C cold-resistant
ATEX	ATEX optional
Min. ambient temperature	-15 °C
Max. ambient temperature	70 °C
Min. medium temperature	-15 °C
Max. medium temperature	70 °C
Medium	Compressed air
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	1 mg/m ³
Max. particle size	50 µm
Weight	1 kg
Material	
Housing material	Aluminum Polyamide, fiber-glass reinforced
Seal material	Acrylonitrile butadiene rubber Polyurethane
Part No.	R412000242

5/2-directional valve, Series CD12, single solenoid

R412000242

CD12

2025-12-10

Technical information

*Note: Basic valves feature a maximum working pressure of 16 bar. When combined with standard CNOMO pilots, the maximum working pressure is 10 bar.

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).


5/2-directional valve, Series CD12, single solenoid

R412000242

CD12

2025-12-10

Dimensions



- 1) Valve plug connector 2) Coil can be rotated at 90° intervals 3) Manual override
4) Port X (only for externally piloted valves) 5) Exhaust port of piston 6) Pilot valve exhaust, M5