

Subbase

R412000631

ISO 15407-1, Base and end plates



Technical data

Industry
Industrial

Type
Manifold strip

Direction of pneumatic port (1)
On the side

Compressed air connection input
G 3/8

Frame size
26 mm

Pilot
External

Standards
ISO 15407-1

Working pressure min.
-0.95 bar

Working pressure max
16 bar

Grid dimension
22 mm

Mounting screw
with hexagon socket

Direction of pneumatic port (3,5)
Up

Port exhaust
G 1/4

Exhaust type
Ports separated

Exhaust (3,5)
With directional exhaust (3/5)

Min. ambient temperature
-25 °C

Max. ambient temperature
70 °C

Min. medium temperature
-25 °C

Max. medium temperature
70 °C

Medium
Compressed air

Tightening torque for mounting screws
4 Nm

Material

Material base plate
Aluminum

Part No.
R412000631

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

Dimensions

