


# 3/2-directional valve, Series CD04

2023-09-07

R412005941

## Series CD04

Qn = 900l/min



## Technical data

Industry	Industrial
Activation	Pneumatically
Valve type	Spool valve, positive overlapping
Valve function	NC/NO
Sealing principle	soft seal
Connection type	Pipe connection

Compressed air connection input	M10x1
Compressed air connection output	M10x1
Compressed air connection, exhaust	M10x1
Compressed air connection pilot input	M10x1

Nominal flow Qn 900 l/min

Working pressure min.	-0.95 bar
Working pressure max.	10 bar
Control pressure min.	3.5 bar
Control pressure max.	10 bar
Min. ambient temperature	-15 °C

# 3/2-directional valve, Series CD04

2023-09-07

R412005941

Max. ambient temperature	65 °C
Min. medium temperature	-15 °C
Max. medium temperature	65 °C
Medium	Compressed air
Oil content of compressed air min.	0 mg/m <sup>3</sup>
Oil content of compressed air max.	1 mg/m <sup>3</sup>
Max. particle size	50 µm
Weight	0.29 kg

## Material

Housing material	Die cast zinc Polyamide fiber-glass reinforced
Seal material	Acrylonitrile butadiene rubber
Part No.	R412005941

## Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

## Dimensions in mm

