


3/2-directional valve, Series CD04

2023-09-01

R412013298

Series CD04

Qn = 900l/min



Technical data

Industry	Industrial
Activation	Pneumatically
Valve type	Spool valve, positive overlapping
Valve function	NC/NO
Sealing principle	soft seal
Connection type	Pipe connection
Standard compressed air connection	according to ANSI B1.20.3
Compressed air connection input	1/8-27 NPTF
Compressed air connection output	1/8-27 NPTF
Compressed air connection, exhaust	1/8-27 NPTF
Compressed air connection pilot input	1/8-27 NPTF
Nominal flow Qn	900 l/min
Working pressure min.	-0.95 bar
Working pressure max	10 bar
Control pressure min.	3.5 bar
Control pressure max.	10 bar

3/2-directional valve, Series CD04

2023-09-01

R412013298

Min. ambient temperature	-15 °C
Max. ambient temperature	65 °C
Min. medium temperature	-15 °C
Max. medium temperature	65 °C
Medium	Compressed air
Oil content of compressed air min.	0 mg/m ³
Oil content of compressed air max.	1 mg/m ³
Max. particle size	50 µm
Weight	0.29 kg

Material

Housing material	Die cast zinc Polyamide fiber-glass reinforced
Seal material	Acrylonitrile butadiene rubber
Part No.	R412013298

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

Dimensions in inches

