
Valve plug connector, series CON-VP

R412024835

General series information AVENTICS Series CON-VP Valve plug connectors with cable

■ The AVENTICS Series CON-VP-with cable offers valve plug connectors with cables of various length, used to connect various valve Series and sensors. The Series covers connector types of Form A, B, B Industry, C and C Industry complying with standards EN 175301-803 (Form A), ISO 6952 (Form B) and ISO 15217 (Form C)





Technical data

Industry
Type
Valve plugs
Cable
Operational voltage
Operating voltage AC max.
Operating voltage DC, max.
Industrial
Valve plugs
with cable
24 V AC/DC
24 V DC

Electrical connection 1, thread size form C, industry

Socket

Electrical connection 1, number of poles 4-pin
Cable exit 1 angled

Cable exit angle 90°

Electrical connection 2, type open cable ends
Electrical connection 2, number of poles 3-pin

Contact assignment 2+E
Number of wires 3

Shielding unshielded



Electrical connection 1, type

Cable length 10 m **IP67** Protection class Protective circuit Varistor -25 °C Min. ambient temperature 70 °C Max. ambient temperature 4 A Max. current with LED Yellow 0.75 mm² Wire cross-section Mounting screw tightening torque 0.4 Nm Weight 0.59 kg

Material


Housing material Polyamide

Seal material caoutchouc/butadiene caoutchouc

Material cable sheath Polyvinyl chloride Part No. R412024835



Dimensions



L = length

