AVENTICS Series CON-MP Multipole plugs with cable

The AVENTICS Series CON-MP-with cable offers cables with a multipol plug like D-SUB with various numbers of pins and different length, optimized for our focused valve system Series like AV Also C/2 connectors for Valve systems of Series CL03 are available.



Technical data

Industrial Industry Type Multipole Cable with cable 24 V DC Operational voltage Max. operating voltage AC 24 V DC Electrical connection 1, type Socket Electrical connection 1, thread size D-Sub Electrical connection 1, number of poles 25-pin Cable exit 1 straight 180° Cable exit angle

Electrical connection 2, type open cable ends

Electrical connection 2, number of poles 25-pin Number of wires 25

Shielding unshielded

Cable length 3 m
Protection class IP67
Min. ambient temperature -20 °C
Max. ambient temperature 80 °C
Max. current 3 A

Multipole plug, series CON-MP

2024-04-02

R419500454

Material

Housing material Thermoplastic elastomer

Material cable sheath Polyvinyl chloride Part No. R419500454

Technical information

The specified protection class is only valid in assembled and tested state.

The increased wire cross-section of pin 25 is 0.82 mm².


The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in https://www.emerson.com/en-us/support).

Fig. 2









Fig. 1





R419500454

PIN assignment and cable colors cable identification as per DIN 47100



Socket

D-Sub socket, 25 pin

Pin	Color
1	white
2	brown
3	green
4	yellow
5	gray
6	pink
7	blue
8	red
9	black
10	violet
11	gray/pink
12	red/blue
13	white/green
14	brown/green
15	white/yellow
16	yellow/brown
17	white/gray
18	gray/brown
19	white/pink
20	pink/brown
21	white/blue
22	brown/blue
23	white/red
24	brown/red
25	white/black