
Round plug connector, Series CON-RD

R419800109

General series information AVENTICS Series CON-RD Round plug connectors with cable

■ The AVENTICS Series CON-RD-with cable offers cables with round plug connectors for various types like M8x1, M12x1 or 7/8-16UNC and different cable length, optimized for our focused valves with M8x1 or M12x1 connection and electronic systems like AES and G3.





Technical data

Industry Industrial

Type Round plug connectors

Cable with cable

Operational voltage 48 V AC/DC

Operating voltage AC max. 48 V DC

Operating voltage DC, max. 48 V AC

Electrical connection 1, type Socket

Electrical connection 1, thread size M12x1 Electrical connection 1, number of poles 5-pin

Electrical connection 1, coding A-coded

Cable exit 1 angled Cable exit angle 90°

Electrical connection 2, type open cable ends




Number of wires	5
Shielding	shielded
Cable length	2.5 m
Protection class	IP67
Min. ambient temperature	-25 °C
Max. ambient temperature	80 °C
Max. current	4 A
Wire cross-section	0.34 mm ²
Cable-Ø	6 mm
Weight	0.145 kg

Material

Housing material Thermoplastic elastomer

Material cable sheath Polyurethane Part No. R419800109


Dimensions







Pin assignment, socket



(1) BN=brown (2) WH=white 3) BU=blue (4) BK=black (5) GY=grey

