


## AVENTICS Series TC15 Directional valves

The AVENTICS Series TC08/TC15 includes a wide range of spool valves with housings made of high-performance polymers with robust and flexible metal inserts. It is designed for flow rate performances from 800 to 1500 l/min. These directional valves are easy to assemble, making them ideal for applications requiring the highest efficiency in limited spaces.



### Technical data

Industry

Activation

Note

Valve type

Basic valve equipment

Valve function

Actuating control

Sealing principle

Connection type

Manual override

Industrial

Electrically

Operating voltage 24 V AC, 110 V AC, 230 V AC

Spool valve, positive overlapping

Basic valve with coil without valve plug connector

NC/NC

Double Solenoid

Soft seal

Pipe connection

with detent

Standard compressed air connection

Compressed air connection input

Compressed air connection output

Compressed air connection, exhaust

Compressed air connection pilot input

according to ISO 228-1

G 1/4

G 1/4

G 1/4

M5

Nominal flow Qn

1100 l/min

Flow conductance b

0.25

# 2x3/2-directional valve, Series TC15

2024-05-06

R422102150

|                                              |                              |
|----------------------------------------------|------------------------------|
| Flow conductance C                           | 5.9 l/(s*bar)                |
| Min. working pressure                        | -0.9 bar                     |
| Max. working pressure                        | 10 bar                       |
| Min. control pressure                        | 3 bar                        |
| Max. control pressure                        | 10 bar                       |
| Electrical connection type                   | Plug                         |
| Electrical connection size                   | ISO 15217, form C            |
| Connector standard                           | ISO 15217                    |
| Protection class with connection             | IP65                         |
| Operational voltage                          | 230 V AC                     |
| Operational voltage AC at 50 Hz              | 230 V                        |
| Voltage tolerance AC 50 Hz                   | -10% / +10%                  |
| Operational voltage AC at 60 Hz              | 230 V                        |
| Voltage tolerance AC 60 Hz                   | -10% / +10%                  |
| Pilot                                        | Internal                     |
| Coil width                                   | 15.6 mm                      |
| Pilot valve width                            | 15 mm                        |
| Nominal resistance                           | 14700 Ω                      |
| Holding power AC 50 Hz                       | 1.6 VA                       |
| Holding power AC 60 Hz                       | 1.4 VA                       |
| Switch-on power AC 50 Hz                     | 2.2 VA                       |
| Switch-on power AC 60 Hz                     | 2 VA                         |
| Duty cycle                                   | 100 %                        |
| Typ. switch-on time                          | 12 ms                        |
| Typ. switch-off time                         | 16 ms                        |
| Generic immunity standard in accordance with | EN 50082-2                   |
| Valve plug connector                         | Without valve plug connector |
| Min. ambient temperature                     | -10 °C                       |
| Max. ambient temperature                     | 50 °C                        |
| Min. medium temperature                      | -10 °C                       |
| Max. medium temperature                      | 50 °C                        |
| Medium                                       | Compressed air               |
| Min. oil content of compressed air           | 0 mg/m <sup>3</sup>          |
| Max. oil content of compressed air           | 5 mg/m <sup>3</sup>          |
| Max. particle size                           | 5 µm                         |

# 2x3/2-directional valve, Series TC15

2024-05-06

R422102150

---

|                                  |          |
|----------------------------------|----------|
| Mounting on manifold strip       | P-strip  |
| Mounting screw tightening torque | 2.5 Nm   |
| Tightening torque tolerance      | ±0,2 mT  |
| Weight                           | 0.278 kg |

## Material

|                           |                                                                         |
|---------------------------|-------------------------------------------------------------------------|
| Housing material          | Polyamide fiber-glass reinforced                                        |
| Seal material             | Acrylonitrile butadiene rubber<br>Hydrogenated nitrile butadiene rubber |
| Material threaded bushing | Brass<br>Die cast zinc                                                  |
| Material front plate      | Polyamide fiber-glass reinforced                                        |

|          |            |
|----------|------------|
| Part No. | R422102150 |
|----------|------------|

## Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

2x3/2-directional valve, Series TC15

2024-05-06

R422102150

Dimensions

