

2x3/2-directional valve, Series TC15


R422102188

Series
TC15

2024-05-06

AVENTICS Series TC15 Directional valves

The AVENTICS Series TC08/TC15 includes a wide range of spool valves with housings made of high-performance polymers with robust and flexible metal inserts. It is designed for flow rate performances from 800 to 1500 l/min. These directional valves are easy to assemble, making them ideal for applications requiring the highest efficiency in limited spaces.



Technical data

Industry

Activation

Note

Valve type

Valve function

Actuating control

Sealing principle

Connection type

Manual override

Industrial

Electrically

Operating voltage 24 V DC

Spool valve, positive overlapping

NO/NO

Double Solenoid

Soft seal

Pipe connection

without detent

Standard compressed air connection

Compressed air connection input

Compressed air connection output

Compressed air connection, exhaust

Compressed air connection pilot input

according to ISO 228-1

G 1/4

G 1/4

G 1/4

M5

Nominal flow Q_n

Flow conductance b

Flow conductance C

1100 l/min

0.25

5.9 l/(s*bar)

2x3/2-directional valve, Series TC15

R422102188

Series
TC15

2024-05-06

Min. working pressure	-0.9 bar
Max. working pressure	10 bar
Min. control pressure	3 bar
Max. control pressure	10 bar
Electrical connection type	Plug
Electrical connection size	M8
Electrical connection number of poles	4-pin
Connector standard	DIN EN 60947-5-2
Protection class acc. to DIN EN 61140	Class III
Protection class with connection	IP65
Operational voltage	24 V DC
Operational voltage DC	24 V
Voltage tolerance DC	-10% / +10%
Pilot	External Internal
Coil width	15.6 mm
Pilot valve width	15 mm
LED status display	Yellow
Power consumption DC	2.2 W
Nominal resistance	280 Ω
Duty cycle	100 %
Typ. switch-on time	12 ms
Typ. switch-off time	16 ms
Generic immunity standard in accordance with	EN 50082-2
Min. ambient temperature	-10 °C
Max. ambient temperature	50 °C
Min. medium temperature	-10 °C
Max. medium temperature	50 °C
Medium	Compressed air
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	5 mg/m ³
Max. particle size	5 µm
Mounting on manifold strip	P-strip
Mounting screw tightening torque	2.5 Nm
Tightening torque tolerance	±0,2 mT

2x3/2-directional valve, Series TC15

R422102188

Series
TC15

2024-05-06

Weight	0.279 kg
--------	----------

Material

Housing material	Polyamide fiber-glass reinforced
Seal material	Acrylonitrile butadiene rubber Hydrogenated nitrile butadiene rubber
Material threaded bushing	Brass Die cast zinc
Material front plate	Polyamide fiber-glass reinforced

Part No.	R422102188
----------	------------

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

R422102188

2024-05-06

Technical drawing of the 3000 series pressure washer, showing three views: top, front, and bottom.

Top View Dimensions:

- Overall width: 21
- Distance between mounting holes: 24, 24
- Mounting hole diameter: 84
- Distance between trigger gun and spray lance: 82
- Connection: (3x) G1/4 (ISO 228)

Front View Dimensions:

- Overall height: 73
- Distance from base to mounting holes: 46,4
- Distance between mounting holes: 100,8
- Overall length: 201,6
- Distance from base to trigger gun: 41
- Distance from base to spray lance: 6,1
- Overall height including trigger gun and spray lance: 53,2
- Distance between mounting holes: 12, 12, 12
- Mounting hole diameter: (3x) Ø5,5

Bottom View Dimensions:

- Overall width: 39,6
- Distance between mounting holes: 13,6, 13,6, 13,6
- Mounting hole diameter: 2
- Connection: M5
- Connection: (2x) G1/4 (ISO 228)

Additional Information:

- Label: 0820XXXXXX
- Pressure rating: max: 10 bar
- Origin: Made in France
- Torque specification: 2,5^{+0,2}_{-0,2} [Nm]

2x3/2-directional valve, Series TC15

R422102188

Series
TC15

2024-05-06

PIN assignment and cable colors for
valve plug connectors



PIN assignment: 1) PIN not assigned 2) PIN not assigned 3) 0 V 4) 24 V 5)
LED Cable colors 1) Brown 2) White 3) Blue 4) Black