


Pilot valve, Series ES05

R422P03356

2024-12-16

Series ES05

$Q_n = [[200 \dots 310] \text{ l/min}]$



Technical data

Industry

Activation

Note

Manual override

Industrial

Electrically

Pilot valve for internal electrical control
without detent

Min. control pressure

3 bar

Max. control pressure

8 bar

Electrical connection size

form C, industry

Operational voltage

24 V DC

Operational voltage DC

24 V

Voltage tolerance DC

-15 % / +10 %

Power consumption DC

2 W

Pilot valve, Series ES05

R422P03356

2024-12-16

Min. ambient temperature	5 °C
Max. ambient temperature	50 °C
Min. medium temperature	5 °C
Max. medium temperature	50 °C
Medium	Compressed air

Mounting screws	Hexalobular socket (TORX) ISO 10664-10
Mounting screw tightening torque	0.9 Nm
Tightening torque tolerance	±0,1 mT
Delivery unit	5 piece

Material

Housing material	Polyamide
Seal material	Acrylonitrile butadiene rubber

Part No.	R422P03356
----------	------------

Technical information

Coil for single wiring connection, rotatable

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.


Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).

Pilot valve, Series ES05

R422P03356

2024-12-16

Dimensions



1) Screws for plastic Ø3

2) rotatable 90°