

QR1-S-RMG standard series

R432000111

2025-04-24

AVENTICS Series QR1 Fittings

AVENTICS Series QR1 push-in connectors with easy, secure mounting are available in many versions: for tubing diameters from 3 to 16 mm, as well as in plastic, metal, and stainless steel variants. QR1 Series offers a cylindric thread that allows repeated connection and release without problems (Quick Release) and captive O-ring guarantees an optimal sealing. Our QR program offers the right solution for every application and industry.



Technical data

Industry	Industrial
Fitting type	Connector, 3x, reducing
Compressed air connection type	External thread
Port G	1/4 NPT
Compressed air connection type 2	Push-in fitting
Port D	Ø1/4
Compressed air connection type 3	Push-in fitting
Compressed air connection 3	Ø5/16
Type	QR1-S-RMG
Min. working pressure	-0.95 bar
Max. working pressure	16 bar
Min. ambient temperature	-20 °C
Max. ambient temperature	80 °C
Delivery quantity	10 piece
Weight	0.032 kg

Material

Housing material	Polyamide
Seal material	Acrylonitrile butadiene rubber

QR1-S-RMG standard series

R432000111

2025-04-24

Material tooth lock washer	Stainless Steel
Material release ring	Polyamide
Material release ring holder	Die cast zinc
	Brass
Surface release ring holder	nickel-plated
Material thread	Brass
Surface thread	nickel-plated
Part No.	R432000111


Technical information

The series QR1 (plastic) and QR2 (metal) can not be combined

Thread seal with captive O-ring

These pneumatic components with NPT or inch thread dimensions are only available from our US sales organization.

Dimensions in inches



Dimensions in inches

Part No.	Port R	Port D	Port G	ØD2	A	B	C1	C2	J	SW
R432000110	Ø3/8	Ø5/16	3/8 NPT	5/16	2.34	0.47	0.83	0.73	0.55	7/32
R432000111	Ø5/16	Ø1/4	1/4 NPT	5/16	2.7	0.43	0.73	0.67	0.47	9/16
R432000112	Ø5/16	Ø5/32	1/4 NPT	3/8	2.51	0.43	0.73	0.63	0.39	9/16

Part No.	X1	Y1	X2	Y2
R432000110	0.63	0.67	0.63	0.55
R432000111	0.63	0.55	0.55	0.47
R432000112	0.63	0.55	0.47	0.39