

Profile cylinder ISO 15552, Series PRA - inch

R480176152

AVENTICS Series PRA Profile cylinders (ISO 15552)

The AVENTICS Series PRA (ISO 15552) cylinders have a compact design profile with integrated sensor slots. The Series PRA (ISO 15552) cylinders can be used for all industries. This includes general automation technology, machine and systems construction, as well as specific industry applications.



Technical data

Industry	Industrial
Piston Ø	32 mm
Stroke	25.4 mm
Ports	1/8 NPT
Functional principle	Double-acting
Cushioning	Pneumatic adjustable cushioning
Magnetic piston	Piston with magnet
Environmental requirements	Industry standard ATEX optional
Piston rod thread - type	External thread
Piston rod thread	7/16-20 UNF
Piston rod	through
Scraper	Standard Industry Scraper
Pressure for determining piston forces	6,3 bar
Retracting piston force	435 N
Extracting piston force	435 N
Min. ambient temperature	-20 °C
Max. ambient temperature	80 °C
Min. working pressure	2 bar
Max. working pressure	10 bar

Profile cylinder ISO 15552, Series PRA - inch

R480176152

Cushioning length	16.5 mm
Cushioning energy	4.8 J
Weight 0 mm stroke	0.58 kg
Weight +10 mm stroke	0.031 kg
Stroke max.	1600 mm
Medium	Compressed air
Min. medium temperature	-20 °C
Max. medium temperature	80 °C
Max. particle size	50 µm
Min. oil content of compressed air	0 mg/m³
Max. oil content of compressed air	5 mg/m³

Material

Piston rod	Stainless Steel
Scraper material	Polyurethane
Seal material	Polyurethane
Material, front cover	Die-cast aluminum
Cylinder tube	Aluminum
End cover	Die-cast aluminum
Nut for piston rod	Steel, chrome-plated
Part No.	R480176152

Technical information

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Cushioning diagram



v_t = Piston velocity [m/s] m = Cushionable mass [kg]

Profile cylinder ISO 15552, Series PRA - inch

R480176152

Overview drawing




NOTE: This overview drawing is only for orientation to indicate where the various accessory parts can be fastened to the cylinder. The illustration has been simplified for this purpose. It is thus not possible to derive the dimensions from this overview.

Profile cylinder ISO 15552, Series PRA - inch

R480176152

Dimensions



S = stroke

Profile cylinder ISO 15552, Series PRA - inch

R480176152

Piston Ø	A -2	ØB d11	BG min.	E	EE inch	EE	H	KK inch	KK	KV
32	22	30	16	46.5	1/8 NPT	G 1/8	47.5	7/16 - 20 UNF	M10x1,25	16
40	24	35	16	53	1/4 NPT	G 1/4	53	1/2 -20 UNF	M12x1,25	18
50	32	40	16	65	1/4 NPT	G 1/4	65	3/4 - 16 UNF	M16x1,5	24
63	32	45	16	75	3/8 NPT	G 3/8	75	3/4 - 16 UNF	M16x1,5	24
80	40	45	17	95	3/8 NPT	G 3/8	95	3/4 - 16 UNF	M20x1,5	30
100	40	55	17	115	1/2 NPT	G 1/2	115	3/4 - 16 UNF	M20x1,5	30
125	54	60	20	140	1/2 NPT	G 1/2	140	1 - 14 UNF	M27x2	41

Piston Ø	KW	ØMM f8	PL	L2	L3 ±0,5	L8	RT	SW	TG	VD
32	5	12	16	16.25	4.5	94±0,4	M6	10	32,5±0,5	5
40	6	16	20	18.25	4.5	105±0,7	M6	13	38±0,5	5
50	8	20	19	25	4.5	106±0,7	M8	17	46,5±0,6	5
63	8	20	24	25	4.5	121±0,8	M8	17	56,5±0,7	5
80	10	25	23.5	33	0	128±0,8	M10	22	72±0,7	5
100	10	25	25	36	0	138±1	M10	22	89±0,7	5
125	13.5	32	33	45	0	160±1	M12	27	110±1,1	7

Piston Ø	WH	ZM
32	26±1,4	146+3/-1,5
40	30±1,4	165+3/-1,5
50	37±1,4	180+3/-1,5
63	37±1,8	195+3/-1,5
80	46±1,8	220+3/-1,5
100	51±1,8	240+3,5/-2
125	65±2,2	290+3,5/-2