

## AVENTICS Series ITS Tie rod cylinders (ISO 15552)

The AVENTICS Series ITS (ISO 15552) cylinders are often chosen when extremely large loads need to be moved efficiently and under control with the familiar ease of operation. The Series ITS (ISO 15552) cylinders are easily configurable to your application needs.

- Up to five tons can be moved by a single Series ITS (ISO 15552) cylinder across a large stroke range from only a few centimetres to 2700 mm
- Allows the simple and cost-effective automation of extremely powerful applications
- Available in piston diameters from 160 mm to 320 mm
- The modular sealing system enables tailor-made solutions for specific applications that function efficiently and minimize maintenance efforts
- Material-optimized design
- Optimized cushioning concept - opportunity to use the elastic cushioning element or pneumatic cushioning
- Analog distance measuring sensors available



## Technical data

|                                        |                                    |
|----------------------------------------|------------------------------------|
| Industry                               | Industrial                         |
| Standards                              | ISO 15552                          |
| Piston Ø                               | 160 mm                             |
| Stroke                                 | 100 mm                             |
| Ports                                  | G 3/4                              |
| Functional principle                   | Double-acting                      |
| Cushioning                             | elastic cushioning                 |
| Magnetic piston                        | Piston without magnet              |
| Environmental requirements             | Industry standard<br>ATEX optional |
| Piston rod thread - type               | External thread                    |
| Piston rod thread                      | M36x2                              |
| Piston rod                             | single                             |
| Scraper                                | Standard Industry Scraper          |
| Pressure for determining piston forces | 6,3 bar                            |
| Retracting piston force                | 11875 N                            |
| Extracting piston force                | 12667 N                            |
| Min. ambient temperature               | -20 °C                             |

|                                    |                     |
|------------------------------------|---------------------|
| Max. ambient temperature           | 80 °C               |
| Min. working pressure              | 2 bar               |
| Max. working pressure              | 10 bar              |
| Impact energy                      | 10 J                |
| Weight 0 mm stroke                 | 12.5 kg             |
| Weight +10 mm stroke               | 0.21 kg             |
| Stroke max.                        | 2700 mm             |
| Medium                             | Compressed air      |
| Min. medium temperature            | -20 °C              |
| Max. medium temperature            | 80 °C               |
| Max. particle size                 | 50 µm               |
| Min. oil content of compressed air | 0 mg/m <sup>3</sup> |
| Max. oil content of compressed air | 5 mg/m <sup>3</sup> |

## Material

|                       |                                |
|-----------------------|--------------------------------|
| Piston rod            | Stainless Steel                |
| Scraper material      | Acrylonitrile butadiene rubber |
| Material tie-rod      | Stainless Steel                |
| Seal material         | Acrylonitrile butadiene rubber |
| Material, front cover | Die-cast aluminum              |
| Cylinder tube         | Aluminum                       |
| End cover             | Die-cast aluminum              |
| Nut for piston rod    | Steel, chrome-plated           |
| Part No.              | R480627670                     |

## Technical information

ATEX-certified cylinders with identification II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135°C Db\_X can be generated in the Internet configurator.

The operating temperature range for ATEX-certified cylinders is -20°C ... 60°C.

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

# Tie rod cylinder ISO 15552, Series ITS

R480627670

Series ITS

2026-07-23

## Overview drawing



NOTE: This overview drawing is only for orientation to indicate where the various accessory parts can be fastened to the cylinder. The illustration has been simplified for this purpose. It is thus not possible to derive the dimensions from this overview.

# Tie rod cylinder ISO 15552, Series ITS

R480627670

Series ITS

2026-07-23

## Dimensions



S = stroke

\*) For cylinders with optional piston rod with internal thread

| Piston Ø | A  | B   | ØB  | BG | DA  | E   | EE    | G    | KK    | KV |
|----------|----|-----|-----|----|-----|-----|-------|------|-------|----|
| 160      | 72 | 65  | 65  | 24 | 167 | 180 | G 3/4 | 56   | M36x2 | 55 |
| 200      | 72 | 75  | 75  | 24 | 210 | 220 | G 3/4 | 54   | M36x2 | 55 |
| 250      | 84 | 90  | 90  | 25 | 262 | 280 | G 1   | 59.5 | M42x2 | 65 |
| 320      | 96 | 110 | 110 | 28 | 336 | 350 | G 1   | 61.5 | M48x2 | 75 |

| Piston Ø | KW | L2 | L8  | L12   | MM | P    | PA | PM   | RT  | SW1 |
|----------|----|----|-----|-------|----|------|----|------|-----|-----|
| 160      | 18 | 53 | 180 | 16    | 40 | 24   | 45 | 35   | M16 | 36  |
| 200      | 18 | 56 | 180 | 16    | 40 | 22.5 | 42 | 30   | M16 | 36  |
| 250      | 21 | 67 | 200 | 20    | 50 | 29   | 46 | 32.8 | M20 | 46  |
| 320      | 24 | 76 | 220 | 23.25 | 63 | 30   | 48 | 37   | M24 | 55  |

| Piston Ø | SW2 | SW3 | TG  | VA | VD | WH  | ZJ    |
|----------|-----|-----|-----|----|----|-----|-------|
| 160      | 27  | 60  | 140 | 6  | 6  | 80  | 260   |
| 200      | 27  | 60  | 175 | 6  | 6  | 95  | 275   |
| 250      | 41  | 80  | 220 | 10 | 31 | 105 | 305.3 |
| 320      | 50  | 95  | 270 | 10 | 34 | 120 | 340.5 |