

## AVENTICS Series CCL-IC Standard cylinders (ISO 21287)

The AVENTICS Series CCL-IC (ISO 21287) cylinders with their compact and clean design can be used in a wide range of applications. Their smooth surface together with their materials, such as anodized aluminium, stainless steel, and NSF-H1 lubricants, make the cylinder ideal for the demanding requirements in the food and beverage industry.

- Compact clean design
- Available in nine sizes covering piston diameters from 16 mm to 100 mm
- Easy to clean anodized surfaces
- Scrapers and lubricants (NSF-H1) are approved for food applications
- Hygienic protective caps for unused mounting holes
- Universal mounting concept for easy assembly, without the need for additional mounting elements



## Technical data

|                                        |                                                                                             |
|----------------------------------------|---------------------------------------------------------------------------------------------|
| Industry                               | Industrial                                                                                  |
| Standards                              | ISO 21287                                                                                   |
| Piston Ø                               | 63 mm                                                                                       |
| Stroke                                 | 125 mm                                                                                      |
| Ports                                  | G 1/8                                                                                       |
| Functional principle                   | Double-acting                                                                               |
| Cushioning                             | elastic cushioning                                                                          |
| Magnetic piston                        | Piston with magnet                                                                          |
| Environmental requirements             | Industry standard<br>suitable for use in food processing<br>ATEX optional<br>High corrosion |
| Piston rod thread - type               | External thread                                                                             |
| Piston rod thread                      | M12x1,25                                                                                    |
| Piston rod                             | single                                                                                      |
| Scraper                                | Standard Industry Scraper                                                                   |
| Pressure for determining piston forces | 6,3 bar                                                                                     |
| Retracting piston force                | 1837 N                                                                                      |
| Extracting piston force                | 1964 N                                                                                      |
| Min. ambient temperature               | -20 °C                                                                                      |

# Compact cylinder ISO 21287, Series CCL-IC

R480668760

Series CCL-  
IC

2026-01-20

|                                    |                     |
|------------------------------------|---------------------|
| Max. ambient temperature           | 80 °C               |
| Min. working pressure              | 1 bar               |
| Max. working pressure              | 10 bar              |
| Impact energy                      | 1.3 J               |
| Weight 0 mm stroke                 | 0.801 kg            |
| Weight +10 mm stroke               | 0.062 kg            |
| Stroke max.                        | 300 mm              |
| Medium                             | Compressed air      |
| Min. medium temperature            | -20 °C              |
| Max. medium temperature            | 80 °C               |
| Max. particle size                 | 50 µm               |
| Min. oil content of compressed air | 0 mg/m <sup>3</sup> |
| Max. oil content of compressed air | 5 mg/m <sup>3</sup> |

## Material

|                       |                 |
|-----------------------|-----------------|
| Piston rod            | Stainless Steel |
| Scraper material      | Polyurethane    |
| Material, front cover | Aluminum        |
| Cylinder tube         | Aluminum        |
| End cover             | Aluminum        |
| Part No.              | R480668760      |

## Technical information

The material for heat-resistant scraper and seal variants (ambient temperature: -10 °C ... 120 °C) is fluorocarbon.

Further options can be generated in the Internet configurator.

LW\*/SW\* Hexagonal key required

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

ATEX-certified cylinders with identification II 2G Ex h IIC T4 Gb / II 2D Ex h IIC T135°C Db\_X can be generated in the Internet configurator.

# Compact cylinder ISO 21287, Series CCL-IC

R480668760

Series CCL-  
IC

2026-01-20

## Dimensions

Ø16 - 63



Ø80 - 100



S = stroke

# Compact cylinder ISO 21287, Series CCL-IC

R480668760

Series CCL-  
IC

2026-01-20

| Piston Ø | A  | B1  | BG min. | E                 | EE   | H   | KK       | KV | KW  | LA  |
|----------|----|-----|---------|-------------------|------|-----|----------|----|-----|-----|
| 16       | 12 | 3.8 | 15      | 29                | M5   | 3.1 | M6       | 10 | 3.2 | 3.5 |
| 20       | 16 | 3.8 | 15      | 36.5              | M5   | 3.1 | M8       | 13 | 4   | 4.8 |
| 25       | 16 | 3.8 | 15      | 40.5              | M5   | 3.1 | M8       | 13 | 4   | 4.8 |
| 32       | 19 | 3.8 | 16      | 49.5              | G1/8 | 3.1 | M10x1.25 | 17 | 5   | 4.8 |
| 40       | 19 | 3.8 | 16      | 57.5              | G1/8 | 3.1 | M10x1.25 | 17 | 5   | 4.8 |
| 50       | 22 | 3.8 | 16      | 69.5              | G1/8 | 3.1 | M12x1.25 | 18 | 6   | 4.8 |
| 63       | 22 | 3.8 | 16      | 79.5              | G1/8 | 3.1 | M12x1.25 | 18 | 6   | 4.8 |
| 80       | 28 | 3.8 | 17      | 98 / ISO 21287:96 | G1/8 | 3.1 | M16x1.5  | 24 | 8   | 0   |
| 100      | 28 | 3.8 | 17      | 115.5             | G1/8 | 3.1 | M16x1.5  | 24 | 8   | 0   |

| Piston Ø | LA1 | LW  | LW*  | MM f8 | PL  | RR min. | RT  | SW | SW* | TG        |
|----------|-----|-----|------|-------|-----|---------|-----|----|-----|-----------|
| 16       | 3.5 | 3.2 | 3.2  | 8     | 5   | 3.2     | M4  | 7  | 7   | 18 ±0,4   |
| 20       | 4.6 | 3.7 | 3.7  | 10    | 5   | 4.1     | M5  | 8  | 8   | 22 ±0,4   |
| 25       | 4.6 | 3.7 | 3.7  | 10    | 5   | 4.1     | M5  | 8  | 8   | 26 ±0,4   |
| 32       | 4.8 | 5   | 5*   | 12    | 7.5 | 5.1     | M6  | 10 | 10* | 32,5 ±0,5 |
| 40       | 4.8 | 5   | 5*   | 12    | 7.5 | 5.1     | M6  | 10 | 10* | 38 ±0,5   |
| 50       | 4.8 | 5.7 | 4,8* | 16    | 7.5 | 6.4     | M8  | 13 | 13* | 46,5 ±0,6 |
| 63       | 4.8 | 5.7 | 4,8* | 16    | 7.5 | 6.4     | M8  | 13 | 13* | 56,5 ±0,7 |
| 80       | 0   | 7   | 6,4* | 20    | 7.5 | 8.4     | M10 | 16 | 16* | 72 ±0,7   |
| 100      | 0   | 7.5 | 6,4* | 25    | 7.5 | 8.4     | M10 | 21 | 21* | 89 ±0,7   |

| Piston Ø | WH       | ZA +S | ZB+S |
|----------|----------|-------|------|
| 16       | 4,8 ±1,4 | 36    | 40.8 |
| 20       | 6 ±1,4   | 37    | 43   |
| 25       | 6 ±1,4   | 39    | 45   |
| 32       | 7 ±1,6   | 44    | 51   |
| 40       | 7 ±1,6   | 45    | 52   |
| 50       | 8 ±1,6   | 45.5  | 53.5 |
| 63       | 8 ±1,6   | 49    | 57   |
| 80       | 10 ±2    | 54    | 64   |
| 100      | 10 ±2    | 67    | 77   |

# Compact cylinder ISO 21287, Series CCL-IC

R480668760

Series CCL-  
IC

2026-01-20

## Overview drawing



NOTE: This overview drawing is only for orientation to indicate where the various accessory parts can be fastened to the cylinder. The illustration has been simplified for this purpose. It is thus not possible to derive the dimensions from this overview.

# Compact cylinder ISO 21287, Series CCL-IC

R480668760

Series CCL-  
IC

2026-01-20

## Dimensions

Ø80 - 100

