



AVENTICS Series RPC Round cylinders

The AVENTICS Series RPC round profile cylinders offer a wide variety of connection options. They are easy to clean and suitable for packaging applications in the food industry due to food grade lubricants. The Series RPC can also be used in standard applications across machine automation needs.



Technical data

Industry	Industrial
Standards	ISO 6431
Type	Version: ISO-type
Piston Ø	40 mm
Stroke	200 mm
Ports	G 1/4
Functional principle	Double-acting
Cushioning	Pneumatic adjustable cushioning
Magnetic piston	Piston with magnet
Environmental requirements	Industry standard ATEX optional
Piston rod thread - type	External thread
Piston rod thread	M12x1,25
Piston rod	single
Scraper	Standard Industry Scraper
Pressure for determining piston forces	6,3 bar
Retracting piston force	660 N
Extracting piston force	790 N
Min. ambient temperature	-20 °C
Max. ambient temperature	80 °C

Min. working pressure	1 bar
Max. working pressure	10 bar
Cushioning length	19 mm
Cushioning energy	9 J
Weight 0 mm stroke	0.58 kg
Weight +10 mm stroke	0.024 kg
Stroke max.	1200 mm
Medium	Compressed air
Min. medium temperature	-20 °C
Max. medium temperature	80 °C
Max. particle size	50 µm
Min. oil content of compressed air	0 mg/m ³
Max. oil content of compressed air	5 mg/m ³
Clamping piece for magnetic field sensor necessary	Clamping piece for magnetic field sensor necessary

Material

Piston rod	Stainless Steel
Scraper material	Polyurethane
Seal material	Polyurethane
Material, front cover	Aluminum
Cylinder tube	Stainless Steel
End cover	Aluminum
Nut for piston rod	Steel, chrome-plated
Part No.	R481609436

Technical information

ATEX-certified cylinders with identification II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135°C Db_X can be generated in the Internet configurator.

The operating temperature range for ATEX-certified cylinders is -20°C ... 60°C.

The pressure dew point must be at least 15 °C less than ambient and medium temperature and may not exceed 3 °C.

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in <https://www.emerson.com/en-us/support>).


Round cylinder, Series RPC

R481609436

Series RPC

2025-07-18

Dimensions



S = stroke

Piston $\emptyset$	A	BE	BF	$\emptyset CD$ H8	$\emptyset D1$	$\emptyset D2$	E	EE	EW	KK
32	22	M30x1,5	20	10	36	33,6	37	G 1/8	26	M10x1,25
40	24	M38x1,5	23	12	45	41,6	45	G 1/4	28	M12x1,25
50	32	M45x1,5	24	12	55	52,4	55	G 1/4	32	M16x1,5
63	32	M45x1,5	26,5	16	69	65,4	69	G 3/8	40	M16x1,5

Piston $\emptyset$	KX	KY	L	$\emptyset MM$	M1	M2	M3	MR	P	SW2
32	16	5	92	12	9,5	9,5	4,5	10,5	24	10
40	18	6	107	16	11,5	11,5	5	13	21	13
50	24	8	110	20	11,5	11,5	5	13	25	17
63	24	8	125	20	13	13,5	5	17	31	17

Piston $\emptyset$	VA	WF	XC
32	16	27	143
40	19	32	160
50	18,5	35	170
63	23	35	191


Round cylinder, Series RPC

R481609436

Series RPC

2025-07-18

Overview drawing



NOTE: This overview drawing is only for orientation to indicate where the various accessory parts can be fastened to the cylinder. The illustration has been simplified for this purpose. It is thus not possible to derive the dimensions from this overview.